

MATERIAL SAFETY DATA SHEET
MSDS Number: 00026 Effective Date: 10/15/11 Page: 1 of 3
Product Name: TPR² FIRE RETARDANT ; F10 SERIES

Product Name: Fireshell® NFPA 286 compliant Coatin
Product Code: TPR² Fireshell® F10 series



PERSONAL PROTECTION INDEX	
A	☒
B	☒ + ☒
C	☒ + ☒ + ☒
D	☒ + ☒ + ☒ + ☒
E	☒ + ☒ + ☒ + ☒ + ☒
F	☒ + ☒ + ☒ + ☒ + ☒ + ☒
G	☒ + ☒ + ☒ + ☒ + ☒ + ☒ + ☒
H	☒ + ☒ + ☒ + ☒ + ☒ + ☒ + ☒ + ☒
I	☒ + ☒ + ☒ + ☒ + ☒ + ☒ + ☒ + ☒ + ☒
J	☒ + ☒ + ☒ + ☒ + ☒ + ☒ + ☒ + ☒ + ☒ + ☒
K	☒ + ☒ + ☒ + ☒ + ☒ + ☒ + ☒ + ☒ + ☒ + ☒ + ☒

1
0
0
G

SECTION I - COMPANY IDENTIFICATION

Manufacturer: TPR²
Address: 36 Plains Rd City: Essex
State: Ct Zip: 06426
 Emergency Telephone Number: CHEMTREC 1 800 424 9300
Information Telephone Number: 1-203-756-TPR2 Fax: 1-203-756-8779
MSDS Prepared By: Chemistry Dept, TPR²
Product Use: Flame Retardant

SECTION II – HAZARDOUS INGREDIENTS/ SARA III INFORMATION

Reportable Component	CAS NO.	%	EXPOSURE LIMITS

*** No reportable quantities of Hazardous ingredients are Present ***

*** This product contains no hazardous ingredients as defined under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200 ***

SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: N/A **WPG (H20=8.33):** 10.9 - 11.3#/gal
DENSITY: 1.3 **APPEARANCE AND ODOR:** N/A
VAPOR DENSITY: Heavier than air **EVAPORATION RATE:** Slower than butyl acetate
V.O.C.: 74g/l

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/A **METHOD USED:** N/A
FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: N/A **UPPER:** N/A
EXTINGUISHING MEDIA: N/A.
FIRE FIGHTING INSTRUCTIONS: Wear a self-contained breathing apparatus and protective clothing to prevent skin and eye contact in fire situations. If large amount of chemicals present, evacuate anyone not properly protected.
UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may rupture when exposed to extreme heat.

SECTION V – REACTIVITY DATA

STABILITY: Stable **HAZARDOUS POLYMERIZATION:** Will not occur
CONDITIONS TO AVOID: None **INCOMPATIBILITY:** Oxidizing materials can cause reaction.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Carbon monoxide and/or carbon dioxide may be released when exposed to very high temperatures.

MATERIAL SAFETY DATA SHEET

MSDS Number: 00026 Effective Date: 10/15/11 Page: 2 of 3

Product Name: TPR² FIRE RETARDANT ; F10 SERIES

SECTION VI- HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Inhalation: May cause headaches.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Eye Contact: Direct contact irritates slightly with redness and swelling.

SKIN OBSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Skin Contact: Can cause irritation .

INJECTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Ingestion: Can cause gastrointestinal irritation.

HEALTH HAZARDS (Acute and Chronic):

Acute: Eyes: Slight irritation with redness. Skin: No adverse effect. Inhalation: Irritates respiratory passage. Ingestion: Large amounts may cause digestive discomfort. Chronic: None Known

*** CARCINOGENICITY ***

Product/Similar Product:

NTP CARCINOGEN: No

IARC MONOGRAPHS: No

OSHA REGULATED: No

Component:

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

Dermatitis, respiratory tract irritation.

EMERGENY AND FIRST AID PROCEDURES:

Inhalation overexposure: Move person to fresh air. If breathing is difficult, administer Oxygen. If breathing has stopped, give artificial respiration and get medical attention. Eye contact: Flush with large amunts of water for 15 minutes. Skin contact: Wash thoroughly with soap and water. Remove contaminated clothing.

SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Dike spill area and cover with inert, absorbent material, and remove to disposal container. Mop with mild detergent or cleaning solution. Observe all federal, State and local laws.

WASTE DISPOSAL METHOD:

Consult Local, State and Federal waste regulations before disposing into approved waste landfills. Obey relevant laws.

*** DO NOT INCINERATE CLOSED CONTAINERS ***

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Handling: no special precautions. Storage: Keep from freezing. Use reasonable care.

OTHER PRECAUTIONS:

*** BEFORE USING ANY PRODUCT, READ THE PRODUCTS LABEL ***

SECTION VIII – CONTROL MEASURES

WORK PRACTICES:

MATERIAL SAFETY DATA SHEET
MSDS Number: 00026 Effective Date: 10/15/11 Page: 3 of 3
Product Name: TPR² FIRE RETARDANT ; F10 SERIES

N/A

RESPIRATORY PROTECTION:

When working with this material, Use approved mechanical filters to remove airborne particulate.

VENTILATION:

Local exhaust as required by job conditions to keep TLV below acceptable limits. Refer to OSHA regulations 29 CFR Part 1910.94.

PROTECTIVE GLOVES:

Gloves recommended for protection of skin.

EYE PROTECTION:

Use safety eyewear with splash guards or side shields.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Wear protective clothing

WORK/HYGENIC PRACTICES:

Eye wash and safety showers in the workplace are recommended. Personnel should wash thoroughly after handling product. Always wash-up before eating, smoking or using the toilet facilities.

RECOMMENDED EXPOSURE LIMITS:

N/A

SECTION IX - DISCLAIMER

To the best of our knowledge, The information contained herein is accurate, obtained from sources believed by TPR² Corporation to be accurate at the time of preparation. TPR² Corporation does not assume any legal responsibility for use or reliance upon same.

*** BEFORE USING ANY PRODUCT READ IT'S LABEL ***